



Microline Dot Matrix Printers

ML390 Turbo ML391 Turbo 24-Pin Dot Matrix Printer

A versatile forms printer with 24-pin print head for improved print quality

The ML390 Turbo/ML391 Turbo narrow and wide carriage printers offer excellent flexibility to users who rely on one printer to perform a wide variety of tasks. Easy to use, highly reliable and with very low running costs, the ML390 Turbo/ML391 Turbo are ideal for retail, small business and office applications.

Highlights:

- 80/136 column dot matrix printers
- 24-pin print head with OKI Printing Solutions reliability
- Up to 390 characters per second print speed
- Multi-part paper-handling (original + 4 copies)
- Ideal for general use and printing of invoices, statements, management information etc



ML390 Turbo/ ML391 Turbo

		ML390 Turbo	ML391 Turbo
General	Number of pins	24	
	No. of multi-part forms	5 (one original + 4 copies)	
Speed and throughput	Utility (12cpi & 10cpi)	312cps	260cps
	Letter quality (12cpi & 10cpi)	104cps	87cps
	Fastest print speed	390cps	390cps
Font & print features	Carriage width (10cpi)	80 columns	136 columns
	Max. in compression mode	160 columns	272 columns
	Character pitch	10/12/15/17.1/20 pitch & proportional	
	Graphics resolution	Up to 360 x 360 dpi	
	Typeface & Font	Courier (Scalable), Roman (Scalable), Swiss (Scalable), Prestige, Gothic, Swiss Bold, Utility, Orator, OCR-A, OCR-B + Barcodes	
Emulations & Interfaces	Printer emulations	Epson LQ Esc/P2, IBM ProPrinter X24/XL24	
	Standard interfaces	Centronics Parallel + USB	
	Optional interfaces	Serial RS 232C , Serial RS 422A, Current Loop RS 232C	
Paper handling	Continuous paper	76-254	76-406mm
	Continuous envelopes	165 x 91mm	239 x 102mm
	First printable line (from top of page)	0.5mm	
	Standard	Rear push tractors, Paper parking, Low tear-off, Autoload single sheet	
	Optional	Pull tractor, Single/dual bin cut-sheet feeder, Roll paper stand (ML390T only), Bottom tractors with metal, Long-life tear-off bar	
Physical	Dimensions (HxWxD)	116 x 398 x 345mm	116 x 552 x 345mm
	Weight	6.9kg	8.9kg
	Memory	128KB	
	Noise level	54dB(A)/ 50dB(A) (quiet mode)	
Power	Power requirements	230V AC	
	Frequency	50/60Hz	
Reliability	Print head life	200 million characters	
	Ribbon life	2 million characters in utility mode at 10cpi (re-inking cartridge)	
	MTBF	10,000 hours	

Consumables Information: Only use genuine OKI Printing Solutions Original consumables to ensure the best quality and performance from your hardware. Non OKI Printing Solutions Original products may damage your printer's performance and invalidate your warranty. Specifications subject to change without notice. All trademarks acknowledged.

OKI DATA CORPORATION.
4-11-22 Shibaura, Minato-Ku
Tokyo 108-8551 Japan
Tel: (81) 3 5445 6452
Fax: (81) 3 5445 6456
WWW.OKIDATA.CO.JP

OKI DATA (SINGAPORE) PTE LTD.
78 Shenton Way #09-01
Lippo Centre
Singapore 079120
Tel: (65) 6221 3722
Fax: (65) 6421 1688
WWW.OKI.COM.SG

OKI DATA (SINGAPORE) PTE LTD.
Malaysia Rep. Office
Suite 21.03, 21st Floor
Menara IGB, Mid Valley City
59200 Kuala Lumpur, Malaysia
Tel: (03) 2287 1177
: 1800 88 1177 (Toll Free)
Fax: (03) 2287 1166
WWW.OKI.COM.MY

OKI SYSTEMS (THAILAND) LTD.
1168/81-82 Lumpini Tower,
27th Floor Rama IV Road,
Tungmahamek, Sathorn
Bangkok 10120
Tel: (662) 679 9235
Fax: (662) 679 9243/245
WWW.OKISYSTHAI.COM



As an ENERGY STAR Partner, Oki has determined that this product meets the ENERGY STAR guidelines for energy efficiency.

OKI
PRINTING SOLUTIONS